

# BUILDER SERIES

W I N D O W S




## 100 SLIDING PATIO DOOR



**MORE VALUE. MORE PERFORMANCE.  
MORE SOLUTIONS.**

If you're looking for a door that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy efficient, offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.





# 100 SLIDING PATIO DOOR



## STANDARD FEATURES

- Full-perimeter weatherstripping for air-tight performance and smooth operation
- Exterior water-repellent preservative treated wood components are primed and ready for acrylic latex paints – also available in natural wood exterior for staining
- Natural wood interior ready for staining to match any interior décor—also available with primed interior for painting
- 4 9/16" jamba eliminates extensive drywall work
- Energy-efficient warm edge insulating tempered glass
- Adjustable rollers
- Composite sill, combines wood, aluminum and vinyl
- Standard handle configuration features a taupe exterior handle with a wood interior handle



## OPTIONS

### GLASS OPTIONS:

Low-E, HP glass, tinted, obscure and tempered

### GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured, 1" contoured styles; 7/8" and 1 1/16" removable grilles

### PRODUCT CONFIGURATION:

Matching side lites, fixed panels, transoms, segmented transoms and a wide selection of architectural shapes

### COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

## THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
3/4" IGU Clear	2.08	0.48	0.62	0.65
3/4" IGU Low-E	2.94	0.34	0.29	0.55
3/4" IGU HP Glass	3.33	0.30	0.29	0.55

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Available Low-E option.
2. Optional HP Glass combines Low-E with argon gas fill for high performance.

