

PRO SERIES

W I N D O W S



800 DOUBLE HUNG



SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.

There's a clear choice when it comes to finding the style and durability you want in windows — Ply Gem Windows Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.





800 DOUBLE HUNG



STANDARD FEATURES

- Rigid, form-fitting PVC cladding on sash and frame being fully welded at top two corners of the frame; weather-tight with a clean appearance
- Interior glazed sash for optimum weatherability and curb appeal
- Integral exterior face groove allows for easy mulling
- Energy-efficient Warm Edge insulating glass enhanced energy performance
- Pre-punched nailing fin makes installation easy and provides continuous flashing for added protection
- Standard Easy-Tilt sash for simple cleaning of exterior glass
- Inverted block-and-tackle balance system ensures smooth and consistent operation of sash
- Select clear wood interior ready for paint or stain



OPTIONS

GLASS OPTIONS:

Low-E, HP glass, tinted, tempered and obscure

INTERIOR WOOD FINISH OPTIONS

Select clear wood or pre-finished white

GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured, 7/8" and 1 1/4" simulated-divided-lite (SDL) with shadow bar; removable 7/8" or 1 1/16" wood grilles

PRODUCT CONFIGURATION:

Twins, side lites, fixed, combinations, bays, circle heads, quarter circles, ellipticals, transoms, true radius, arches and a wide variety of architectural shapes

COLOR OPTIONS:

Exterior cladding offered in white and sandalwood; cam-action sash locks offered in standard taupe and white



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
5/8" Clear	2.04	0.49	0.58	0.61
5/8" Low-E	2.70	0.37	0.28	0.52
HP Glass ³	3.03	0.33	0.27	0.52

All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass, no grilles and Warm Edge spacer system.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Most units are rated DP50 straight out of the box.
2. Available option.
3. Optional HP glass combines Low-E with argon gas fill for high performance.

