

# PRO SERIES

W I N D O W S

 **Ply GEM**  
WINDOWS



## 800 FRENCH SLIDING PATIO DOOR



**SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.**

There's a clear choice when it comes to finding the style and durability you want in patio doors – Ply Gem Windows Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.



[www.plygemwindows.com](http://www.plygemwindows.com)



# 800 FRENCH SLIDING PATIO DOOR



## STANDARD FEATURES

- Combination extruded rigid PVC frame exterior cladding and pultruded fiberglass door panel exterior cladding
- Composite sill combines wood, aluminum and vinyl
- Multi-point locking system
- Energy-efficient warm edge insulating tempered glass for enhanced energy performance
- Pre-punched nailing fins with overlapping corners applied
- Color-coordinated top-hanging aluminum framed screen with fiberglass mesh
- 1 3/4" door panels with wide stiles and rails for true French look
- Factory-standard clear wood 4 9/16" jamb
- Adjustable rollers and security foot bolt
- Multi-point hardware available in a variety of finishes
- Natural wood interior ready for paint or stain



## OPTIONS

### GLASS OPTIONS:

Low-E, HP (Low-E/argon), tinted, Low-E tinted and obscure

### GRILLE OPTIONS:

7/8" and 1 1/4" simulated-divided-lite (SDL) with shadow bar; grilles-between-the-glass (GBG) in 1/2" and 7/8" flat, 5/8" sculptured styles; removable 7/8" or 1 1/16" wood grilles

### PRODUCT CONFIGURATION:

Fixed panels, transoms and a wide variety of architectural shapes

### HARDWARE FINISH OPTIONS:

Solid bright brass, antique brass, oil rubbed or satin nickel interior and exterior handle sets

### EXTENSION JAMBS:

Available custom 6 9/16"

### EXTERIOR CLADDING COLOR OPTIONS:



### PRO SERIES 800 FRENCH SLIDING PATIO DOOR

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
3/4" Clear	2.22	0.45	0.50	0.52
3/4" Low-E	2.94	0.34	0.24	0.44
3/4" HP Glass	3.23	0.31	0.24	0.44

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Available option.
2. HP glass option combines Low-E with argon gas fill for high performance.