

# PRO SERIES

W I N D O W S

 **Ply GEM**  
WINDOWS



## 800 SLIDING PATIO DOOR



**SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.**

There's a clear choice when it comes to finding the style and durability you want in patio doors – Ply Gem Windows Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.



[www.plygemwindows.com](http://www.plygemwindows.com)





# 800 SLIDING PATIO DOOR



## STANDARD FEATURES

- Rigid form-fitting vinyl cladding on door panel and frame for protection from the elements
- Composite sill combines wood, aluminum and vinyl
- Single-point locking system
- Energy-efficient warm edge insulating tempered glass for enhanced energy performance
- Pre-punched nailing fins with overlapping corners applied
- Color-coordinated top-hanging aluminum framed screen with fiberglass mesh
- Factory-standard clear wood 4 9/16" jamb
- Adjustable rollers and security foot bolt
- Solid bright brass interior and color-coordinated exterior handles
- Natural wood interior ready for paint or stain



## OPTIONS

### GLASS OPTIONS:

Low-E, HP (Low-E/argon), tinted, Low-E tinted and obscure



### GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured styles; removable 7/8" or 1 1/16" wood grilles



### PRODUCT CONFIGURATION:

Fixed panels, transoms and a wide variety of architectural shapes

### EXTENSION JAMBS:

Available custom 6 9/16"

### EXTERIOR CLADDING COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

### PRO SERIES 800 SLIDING PATIO DOOR

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
3/4" Clear	2.13	0.47	0.62	0.64
3/4" Low-E	2.94	0.34	0.29	0.54
3/4" HP Glass	3.33	0.30	0.29	0.54

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Available option.
2. HP glass option combines Low-E with argon gas fill for high performance.

