

# BUILDER SERIES

W I N D O W S



## 600 DOUBLE HUNG



**MORE VALUE. MORE PERFORMANCE. MORE SOLUTIONS.**

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy efficient, offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.



[www.plygemwindows.com](http://www.plygemwindows.com)





# 600 DOUBLE HUNG



## STANDARD FEATURES

- Dual action sash lock provides security and enhanced performance
- 4 1/16" jambs eliminates extensive drywall work
- Both sash tilt in and remove for safe and easy cleaning of exterior glass (optional Easy-Tilt sash system shown)
- Pre-punched nailing fin with corner gasket for simple installation
- Weatherstripping at top, bottom and check rails for efficient performance and smooth, easy opening and closing
- Rigid form-fitting vinyl cladding on frame, fully welded at top two corners for maximum protection against the elements
- Paint-free all-vinyl sash fully welded at the corners
- Exterior integral face groove allows for easy mulling
- Full-length lift rail along top of bottom sash for convenient opening and closing
- Balances counter-balanced with quiet, adjustable springs for smooth up and down action
- Energy-efficient warm edge insulating glass



## OPTIONS

### GLASS OPTIONS:

Low-E, Low-E<sup>SC</sup>, HP glass, HP<sup>SC</sup> glass, tinted, obscure and tempered

### GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" 5/8" sculptured, 1" contoured styles; 7/8" and 1 1/4" simulated-divided-lite (SDL)

### PRODUCT CONFIGURATION:

Singles, twins, combinations, 30° and 45° angle bays, side lites, stationaries and a wide selection of architectural shapes

### COLOR OPTIONS:



### 600 VINYL-CLAD DOUBLE HUNG

3mm Glass	R Value	NRFC CERTIFIED		
		U Factor	SHGC	VT
5/8" IGU Clear	2.13	0.47	0.59	0.62
5/8" IGU Low-E	2.94	0.34	0.28	0.53
5/8" IGU HP Glass	3.23	0.31	0.28	0.53

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 5/8" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Available Low-E option.
2. Optional HP Glass combines Low-E with argon gas fill for high performance.

