

BUILDER SERIES

W I N D O W S



100 DOUBLE HUNG



MORE VALUE. MORE PERFORMANCE. MORE SOLUTIONS.

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy efficient, offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.





100 DOUBLE HUNG



STANDARD FEATURES

- Natural wood sash and interior ready for staining to match any interior décor – also available with primed interior for painting
- Exterior water-repellent preservative treated wood components are primed and ready for acrylic latex paints – also available in natural wood exterior for staining
- Energy-efficient warm edge insulating glass
- Compression balance system for simple tilt-in cleaning of exterior glass
- 4 9/16" jambs eliminate need for drywall work; custom jamb extensions to 8 9/16"
- Standard white cam-action sash locks and matching white jambliner; optional bronztone cam-action sash locks and matching beige jambliner available
- Routed finger lift-in bottom sash rail for easy operation
- Foam-filled weatherstripping on sash for air-tight performance and smooth operation



OPTIONS

GLASS OPTIONS:

Low-E, HP glass, tinted, obscure and tempered

GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured, 1" contoured styles; 7/8" and 1 1/4" simulated-divided-lite (SDL); 5/8" and 1 1/16" removable grilles

PRODUCT CONFIGURATION:

Singles, twins, combinations, 30° and 45° angle bays, side lites, stationaries and a wide selection of architectural shapes

COLOR OPTIONS:

PRIMED

NATURAL WOOD



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
5/8" IGU Clear	2.08	0.48	0.58	0.61
5/8" IGU Low-E	2.78	0.36	0.28	0.52
5/8" IGU HP Glass	3.13	0.32	0.27	0.52

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 5/8" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Available Low-E option.

2. Optional HP Glass combines Low-E with argon gas fill for high performance.

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

