

M.W
PRO SERIES
W I N D O W S



CLASSIC SLIDING WINDOW



SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.

There's a clear choice when it comes to finding the style and durability you want in windows – Ply Gem Windows MW Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.



CLASSIC SLIDING WINDOW



STANDARD FEATURES

- Classic brick mould profile provides an authentic sculptured appearance that matches traditional exterior millwork
- Interior and exterior accessory grooves allow for easy accessory application
- Easy-gliding sash with maintenance-free nylon pad slider which conveniently lift out for easy cleaning
- Most units structural DP rating of +47/-57 out of the box
- Weather-tight dual action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient warm edge insulating glass for enhanced energy efficiency
- Double-opposed weatherstrip on sash ensures smooth operation, increased weatherability
- Integral nailing fin with welded corners for simple and accurate installation
- Maintenance-free multi-chamber PVC construction with fusion welded corners for durability, weather-tight performance and beauty
- Robust interlock satisfies forced entry requirements and improves structural performance
- Integral $1\frac{1}{16}$ " siding pocket with undersill trim leg allows for simple and secure siding installation



OPTIONS

GLASS OPTIONS:

Low-E, HP (Low-E/argon), tinted, tempered and obscure



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat $\frac{7}{8}$ ", sculptured $\frac{5}{8}$ " styles

EXTENSION JAMBS:

Custom to 6 $\frac{9}{16}$ " in primed or natural "clear" wood



PRODUCT CONFIGURATION:

Available in single (even lite), $\frac{1}{4}$ - $\frac{1}{2}$ - $\frac{1}{4}$ and $\frac{1}{3}$ - $\frac{1}{3}$ - $\frac{1}{3}$

COLOR OPTIONS:



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
$\frac{3}{4}$ " Clear	2.08	0.48	0.59	0.62
$\frac{3}{4}$ " Low-E	2.86	0.35	0.28	0.53
HP Glass ³	3.23	0.31	0.28	0.53

All units tested in accordance with ASTM standards; rated in accordance with International Residential Code; and witnessed by an independent AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: $\frac{3}{4}$ " IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Available option.
2. Select call sizes in the single panel configuration are rated DP45 straight out of the box.
3. HP glass option combines Low-E with argon gas fill for high performance.

