



CASEMENT & AWNING











PLY GEM MIRA PREMIUM SERIES WINDOWS HAVE BEEN GREEN APPROVED BY THE NAHB RESEARCH CENTER.

This means you can be assured that Ply Gem Mira Premium Series windows comply with specific green practice criteria in the National Green Building Standard. Visit www.GreenApprovedProducts.com for more details.

NFFRC THERMAL PERFORMANCE

		NFRC CERTIFIED		
	R Value	U Factor	SHGC	VT
WITH WARM EDGE				
³/₄" HP Glass	3.23	0.31	0.20	0.38
³/₄″ HP ^{sc} Glass	3.23	0.31	0.15	0.30
WITH WARM EDGE+				
³/ ₄ " HP Glass	3.45	0.29	0.20	0.38
³/ ₄ " HP ^{sc} Glass	3.45	0.29	0.15	0.30

All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: ¾" IGU, 3mm glass, no grilles and Warm Edge spacer system and Warm Edge+ spacer system.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

Most unit sizes ENERGY STAR® qualified in most zones and may be eligible for LEED for Homes* credits.



- *LEED for Homes is a rating system of the U.S. Green Building Council that promotes the design and construction of high-performance green homes.
- 1. Most units are rated DP60 straight out of the box. 2. HP glass combines Low-E with argon gas fill for
- high performance.
 3. Optional HP^{sc} glass combines Solar Cooling optimized Low-E with argon gas fill for high performance for warmer climates.
- 4. Optional Warm Edge+ spacer system for enhanced performance.
- 5. Available option.6. Impact Rated units are available in select sizes and configurations.

EXTERIOR CLADDING COLOR OPTIONS



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

STANDARD FEATURES

- 90° opening sash for greater airflow and easy cleaning
- Sleek fold-down crank handle won't interfere with window treatments
- accurate wood window look
- 4⁹/₁₆" jambs made of clear wood eliminate
- wood; ready for paint or stain to match any interior décor (also available in prefinished white)
- Integral face groove allows for easy mulling and exterior accessory application
- Pre-punched nailing fin for simple installation
- AAMA 2604 paint finish provides superior resistance to chalking and fading
- Energy-efficient Warm Edge insulating HP glass (Low-E/argon gas fill) reduces energy costs while reducing fabric fading
- resist damage from water and fungus
- Durable .050 extruded aluminum cladding on all exterior surfaces resists dings and dents while providing structural integrity





OPTIONS

GLASS OPTIONS:

HP^{SC} glass, Warm Edge+, tinted, tempered, obscure and laminated

GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in $^5/_8$ " and $^7/_8$ " flat, $^5/_8$ " sculptured and 1" contoured in white only; simulated-divided-lite (SDL) available in ¹/₈" and 1 ¹/₄"; ¹/₈" full surround removable wood grilles; 2 ¹/₈" simulated check rail available

EXTERIOR CASING:

180 Brick Mould, 31/4" Williamsburg, 31/2" Flat and Sill Nose

EXTENSION JAMBS:

HARDWARE FINISHES:

White, taupe, sandalwood, bright brass, antique brass, satin nickel and oil rubbed bronze

PRODUCT CONFIGURATION:

Twins, fixed, combinations, bays & bows, circle heads, quarter circles, ellipticals, transoms, true radius, arches and various architectural shapes









